

PATH TO THE FUTURE

Wir stellen vor: den MSI MAG 2244FDE E-Sport-Gaming-Monitor. Dieser hochmoderne Monitor verfügt über ein 24-Zoll-FHD-Display mit einer blitzschnellen Bildwiederholungsrate von 200 Hz und einer schnellen MPRT-Reaktionszeit von 0,5 ms (GtG, Min.). Mit dem MAG 244FDE hast du den nötigen Wettbewerbsvorteil, um deine Gegner in Gaming-Schlachten zu übertreffen und zu besiegen.



SELLING POINTS

- Rapid IPS Panel – Bietet eine Reaktionszeit von 0,5 ms (GtG, Min.), optimiert Bildschirmfarben und -helligkeit.
- 200 Hz Bildwiederholungsrate – Reagiert schneller mit flüssigeren Bildern.
- 0,5 ms (GtG, Min.) Reaktionszeit – Beseitigt Bildschirmlinien und abgehackte Bildraten.
- AI Vision – Die neue AI Vision Technik kann nicht nur Details in dunklen Bereichen sichtbar machen, sondern auch die Gesamthelligkeit verbessern und Farben sättigen.
- Less Blue Light – Verwendet eine Softwarelösung, um die Lichtemission im blau-violetten Bereich des blauen Lichtspektrums zu reduzieren.



1. 5-way Joystick Navigator
2. HDMI™ 2.0b (FHD@200Hz)
3. Display Port 1.2a (HBR2)
4. Headphone out
5. DC-in
6. Kensington Lock



MONITOR
MAG 244FDE
MAG 244F

SPECIFICATION

Model	Part No	9S6-3BC41H-013
	Color	ID1/Black-Black
Display	Screen Size	23.8" (60.45cm)
	Active Display Area (mm)	527.04 (H) x 296.46 (V)
	Curvature	Flat
	Panel Type	Rapid IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.2745(H)x0.2745(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~200Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	54.9~220.18 KHz(H) / 48~200 Hz(V)
	Refresh Rate	200HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	0.5ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	109%/87%
	NTSC (CIE1931 area percentage/overlap)	91%/82%
	sRGB (CIE1976 area percentage/overlap)	126%/99%
	sRGB (CIE1931 area percentage/overlap)	130%/99%
	Adobe RGB (CIE1976 area percentage/overlap)	108%/91%
	Adobe RGB (CIE1931 area percentage/overlap)	96%/84%
	DCI-P3 (CIE1976 area percentage/overlap)	101%/96%
	DCI-P3 (CIE1931 area percentage/overlap)	96%/93%
	Rec.709 (CIE1976 area percentage/overlap)	126%/99%
	Rec.709 (CIE1931 area percentage/overlap)	130%/99%
	Rec.2020 (CIE1976 area percentage/overlap)	72%/72%
	Rec.2020 (CIE1931 area percentage/overlap)	68%/68%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
Schnittstellen	Headphone-out	1
	Lock type	Kensington Lock
	HDMI	1
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.3
Garantie	Warranty	36 Monate Pick-Up & Return
Power	Power Type	External Adaptor 12V 3A
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	17
	Annual Energy Consumption (KWh)	17
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E
	Power Cord Type	C13



MONITOR

MAG 244FDE

MAG 244F

Zubehör	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Abmessungen & Gewicht (Product)	Product Dimension with Stand (WxDxH) (mm)	541.93 x 220.17 x 398.32
	Product Dimension without Stand (WxDxH) (mm)	541.93 x 60 x 322.26
	Stand Dimension (WxDxH) (mm)	317.9 x 220.07 x 142.52
	Weight (Net kg)	2.88
	Weight Without Stand (kg)	2.53
Abmessungen & Gewicht (Verpackung)	Inside Carton Dimension (WxDxH) (cm)	60 x 12.5 x 39.6
	Outer Carton Dimension (WxDxH) (cm)	61.5 x 13.8 x 41.8
	Weight (Gross kg)	4.7
Barcode Info	EAN	4711377330701