

ASUS VA34VCPSR

178° Ultra-wide View Curved Docking Monitor



Key Features



The WQHD resolution is 2.5 times than Full HD, providing much more detailed graphics



Curved Design

Frameless design in 1500R curvature for immersive visual enjoyment



More space to spread out your various work windows for more productive multitasking



USB Type-C Monitor

Full function USB-C connection for video, USB data transmission and supports 96W power delivery



RJ-45

Delivers stable Internet connection and one-cable docking to your laptop with RJ45 and USB-C connection



USB Hub

Satisfies every usage with built-in USB hub and rich connectivity



Eye Care+

ASUS Eye Care+ technology with flicker free and low blue light ensures a comfortable viewing experience




Ergonomic Stand

With an ergonomically-designed stand with tilt, swivel and height adjustments



ASUS DisplayWidget Center lets users easily change monitor settings via an intuitive interface

Specification

Display	Panel Size : Ultra Wide Screen 34-inch (86.43 cm), 21:9 Display Viewing Area (HxV) : 797.2 x 333.7 mm Panel Type : VA Curvature : 1500R True Resolution : 3440 x 1440 Pixel Pitch : 0.2318 mm Brightness(Max) : 300 cd/m ² Contrast Ratio : 3,000:1 ASUS Smart Contrast Ratio (ASCR) : 100,000,000:1 Viewing Angle (CR ≥ 10) : 178°(H)/178°(V) Color Saturation : 85% NTSC Response Time : 4ms (Gray to Gray) Display Colors : 1073.7M (10 bit) Refresh Rate (Max) : 100Hz Flicker Free : Yes	
Video Feature	Blue Light Filter : Yes Trace Free Technology : Yes SPLENDID Technology : 8 Modes (Standard / Scenery / Night View / Game / Theater / sRGB / Reading / Darkroom) Color Temperature Selection : 4 Modes (Cool / Normal / Warm / User) HDCP support : Yes, 2.2 Motion Sync : Yes GamePlus : Yes (Crosshair / Timer / FPS Counter / Display Alignment) QuickFit : 3 modes (Alignment Grid / Document / Photo) Picture-in-Picture/ Picture-by-Picture : Yes VRR Technology : Adaptive-Sync, 48~100Hz DisplayWidget : Yes, DisplayWidget Center Eye Care+ Technology : Yes	
Audio Feature	2W x 2 Stereo RMS	
I/O Ports	Signal Input : USB-C x 1 (DP Alt Mode) DisplayPort 1.4 x 1 HDMI (v2.0) x 1 RJ45 x 1 USB-C Power Delivery : 96W	USB Hub: USB3.2 Gen 1 Type-A x 3 Earphone Jack : Yes, 3.5mm Mini-Jack
	 <p style="text-align: center;">HDMI DisplayPort USB-C USB-A USB-A RJ45 Earphone out</p>	
Signal Frequency	Digital Signal Frequency : HDMI: 30~225 KHz (H) / 48~100 Hz (V) USB-C, DisplayPort: 225~225 KHz (H) / 48~100 Hz (V)	
Power Consumption	Power on (Typical) : 32W Power Saving Mode : < 0.5W Power Off Mode : < 0.3W Voltage : 100-240V, 50 / 60Hz	
Mechanical Design	Tilt : +35° ~ -5° Swivel : +180° ~ -180°	Height Adjustment : 0 ~ 130 mm VESA Wall Mounting : 100 x 100 mm
Security	Kensington lock	
Dimensions	Phys. Dimension with Stand (WxHxD) : 80.93 x (38.10~51.10) x 26.49 cm Phys. Dimension without Stand (WxHxD) : 80.93 x 36.58 x 10.67 cm Box Dimension (WxHxD) : 107.0 x 49.0 x 18.6 cm	
Weight	Net Weight (Esti.) : 9.32 Kg Net Weight without Stand (For VESA Wall Mount) (Esti.) : 6.4 Kg Gross Weight (Esti.) : 14.1 Kg	
Accessories	Power Cord, USB-C cable (optional), DisplayPort cable (optional), HDMI cable (optional), Warranty card, Quick Start Guide	
Compliance Standard	FCC, UL/cUL, ICES-3, CB, CE, ErP, WEEE, ISO 9241-307, UkrSEPRO, CU, CCC, CEL, BSMI, RCM, AU MEPS, VCCI, PSE, PC Recycle, J-MOSS, KC, KCC, e-Standby, Energy Star, TCO, RoHS, CEC, WHQL Windows 10/11, EPEAT Gold, TÜV Flicker-free, TÜV Low Blue Light, FSC Mix	

*Power consumption is measured with screen brightness of 200 nits without audio / USB / or other peripheral connections drawing power.

**All specifications are subject to change without notice