

PATH TO THE FUTURE

Der MAG 274QPFDE X30MV Gaming-Monitor mit 27 Zoll Rapid VA und Mini-LED (1152 Zonen), 2560 x 1440 WQHD und 300 Hz sowie DisplayHDR 1000 für superflüssige Bilder. Hol das Beste aus dir raus.



SELLING POINTS

- Mini-LED - Besseres HDR mit Full-Array-Local-Dimming und 1.152 Zonen für tiefere Schwarztöne und hellere Highlights.
- Rapid VA - Sorgt für intensive und reine Farben beim Gaming.
- VESA DisplayHDR 1000 - VESA-zertifizierte Details, die durch präzise Kontrast- und Schattenanpassung ins Auge fallen.
- Hohe Bildwiederholungsrate von 300 Hz - Liefert flüssige Bilder für schnellere Reaktionen im Spiel.
- Reaktionszeit von 0,5 ms (GtG, min.) - Eliminiert Bildreißen und ruckelige Bildraten.
- Konsolenmodus - Optimiert für nahtlose Kompatibilität mit Spielekonsolen wie PS5 und Xbox Series X|S.
- Quantum Dot-Technik - Liefert über eine Milliarde lebendige Farben mit atemberaubender Klarheit.
- Seitenverhältnisoptionen - Wähle zwischen mehreren Seitenverhältnissen für ein individuelleres Spielerlebnis.



1. 2x HDMI™ 2.1 (WQHD@300Hz)
2. 5-Wege Navigation
3. DisplayPort 1.4a (HBR3)
4. Kopfhörerausgang
5. Stromanschluss
6. Kensington Lock

SPECIFICATION

Model	Part No	9S6-3CF09H-003
	Color	ID1/Black-Black
	Local Dimming	1152 Zones
Display	Screen Size	27" (68.58 cm)
	Active Display Area (mm)	596.736(H) x 335.664(V)
	Curvature	Flat
	Panel Type	Rapid VA
	Resolution	2560x1440 (WQHD)
	Pixel pitch (mm)	0.2331(H)x0.2331(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~300Hz
	HDR (High dynamic range)	VESA DisplayHDR 1000
	SDR Brightness (nits)	400
	Contrast Ratio	5000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	88.56~432.14 KHz(H) / 48~300 Hz(V)
	Refresh Rate	300Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	0.5ms (Min.)
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	131.4%/96.3%
	NTSC (CIE1931 area percentage/overlap)	111.6%/95.9%
	sRGB (CIE1976 area percentage/overlap)	150%/100%
	sRGB (CIE1931 area percentage/overlap)	157%/100%
	Adobe RGB (CIE1976 area percentage/overlap)	129%/99.7%
	Adobe RGB (CIE1931 area percentage/overlap)	116%/99%
	DCI-P3 (CIE1976 area percentage/overlap)	120%/97.3%
	DCI-P3 (CIE1931 area percentage/overlap)	116%/93%
	Rec.709 (CIE1976 area percentage/overlap)	150%/100%
	Rec.709 (CIE1931 area percentage/overlap)	157%/100%
	Rec.2020 (CIE1976 area percentage/overlap)	87%/86%
	Rec.2020 (CIE1931 area percentage/overlap)	83%/83%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
Schnittstellen	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.1 (FRL 6G)
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4a
	DisplayPort HDCP version	2.3
Garantie	Warranty	36 Monate Pick-Up & Return
Power	Power Type	External Adaptor 19V 5.79A
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	TBD
	Annual Energy Consumption (KWh)	TBD
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	TBD
Power Cord Type	C5	

Zubehör	DisplayPort Cable	1
	HDMI Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	Adjustment (Swivel)	-30° ~ 30°
	Adjustment (Height)	0 ~ 110 mm
	Adjustment (Pivot)	-90° ~ 90°
	VESA Mounting	100x100mm
Abmessungen & Gewicht (Product)	Product Dimension with Stand (WxDxH) (mm)	613.10 x 227.90 x 423.53
	Product Dimension without Stand (WxDxH) (mm)	613.10 x 68.77 x 375.31
	Stand Dimension (WxDxH) (mm)	312.53 x 202.38 x 402.73
	Weight (Net kg)	N/A
	Weight Without Stand (kg)	N/A
Abmessungen & Gewicht (Verpackung)	Inside Carton Dimension (WxDxH) (cm)	N/A
	Outer Carton Dimension (WxDxH) (cm)	N/A
	Weight (Gross kg)	N/A
Barcode Info	EAN	4711377298933