

IM C401SRF

MAIN SPECIFICATIONS

GENERAL

| | |
|-------------------------------|---------------------------------|
| Warm-up time | 24 seconds |
| First copy speed: B/W | 6.7 seconds |
| First copy speed: full colour | 7.9 seconds |
| Continuous output speed | BW: 43 cpm, full colour: 40 cpm |
| Memory: standard | 6 GB |
| SSD: standard | 256 GB |
| SSD: optional | 1 TB |
| HDD: optional | 320 GB |
| Weight | 60 kg |
| Dimensions: W x D x H | 615 x 561 x 706 mm |
| Power source | 220 - 240 V, 50 - 60 Hz |

COPIER

| | |
|------------------|------------------------------|
| Multiple copying | Up to 999 copies |
| Resolution | 600 dpi |
| Zoom | From 25% to 400% in 1% steps |

PRINTER

| | |
|-----------------------------|--|
| CPU | ApolloLake E3930 1.3 GHz |
| Printer language: standard | PCL5c PCL6 PostScript 3 (emulation) PDF direct (emulation) |
| Printer language: option | Genuine Adobe® PostScript®3™ XPS PDF Direct from Adobe® |
| Print resolution: maximum | 1,200 x 1,200/1 bit |
| Network interface: standard | Ethernet 10 base-T/100 base-TX/1000 base-T, USB Host IF Type A, USB Device IF Type B, Bluetooth, Wireless LAN (IEEE 802.11 a/b/g/n/ac) |
| Network interface: option | Additional NIC (2nd port) |
| Mobile printing capability | Apple AirPrint, Mopria®, Ricoh Smart Device Connector |
| Network protocol | TCP/IP (IP v4, IP v6) |
| Windows® environments | Windows® 10 Windows® 11 Windows® Server 2016 Windows® Server 2019 Windows® Server 2022 Windows® Server 2025 |
| Mac OS environments | Macintosh OS X v11 or later |
| UNIX environments | UNIX Sun® Solaris HP-UX SCO OpenServer RedHat® Linux Enterprise IBM® AIX |

SCANNER

| | |
|--|--|
| Scanning speed: SPDF (A4 LEF, 200dpi, B/W full colour) | 40 ipm (simplex) - 80 ipm (duplex) |
| Resolution: maximum | 1,200 dpi |
| File formats | Single Page TIFF, Single page JPEG, Single page PDF, Single page High compression PDF, Single page PDF/A, Multi page TIFF, Multi page PDF, Multi page High compression PDF, Multi page PDF/A, Single page Encryption PDF, Multi page Encryption PDF, Single/multi OCR (optional) |
| Scan modes | E-mail, Folder, USB, URL, FTP, E-mail, Folder, USB |

FAX

| | |
|----------------------------|------------------|
| Circuit | PSTN, PBX |
| Compatibility | ITU-T (CCITT) G3 |
| seconds | |
| Modem speed: maximum | 33.6 Kbps |
| 8x7.7 line/mm, 200x200 dpi | |
| MH | |
| MR | |
| MMR | |
| JBIG | |
| Scanning speed | 80 spm |

IM C401SRF

MAIN SPECIFICATIONS

PAPER HANDLING

| | |
|--------------------------------|--|
| Recommended paper size | Standard paper tray(s) (A4, A5, B5), Bypass tray (A4, A5, A6, B5, B6) |
| Paper input: standard | 550 sheets |
| Paper input: bypass (standard) | 100 sheets |
| Paper input: maximum | 2,300 sheets |
| Paper output: max. | 250 sheets |
| Paper weight | Trays (60 - 163 g/m ²), Bypass (60 - 220 g/m ²), Duplex (60 - 163 g/m ²) |
| Paper types | Plain paper, Recycled paper, Special paper, Colour paper, Letterhead, Cardstock, Preprinted paper, Bond paper, Coated paper, Envelope, Label paper |

ECOLOGY

| | |
|--------------------------|---------------|
| Power consumption: max. | < 1,350 W |
| Power consumption: ready | 48.5 W |
| TEC* | 0.48 kWh/week |

* It is a reference value based on the ENERGY STAR Ver.3.2 test method.

INPUT/OUTPUT TRAYS AND FINISHER OPTIONS

| | |
|-----------------------------|--|
| 3x 550-sheet paper tray | Paper size: (A4, A5, B5), Paper weight: (60-163 g/m ²) |
| 250-sheet Internal finisher | Paper size: : A3A4A5A6B3B4B5 Paper weight: : 60-220 g/m ² Stack capacity: : 250 sheets Staple capacity: : 50 sheets Staple paper size: : A3A4A5A6B3B4B5B6 Staple paper weight: : 64-81 g/m ² Staple positions: : TopBottom2 staplesTop-slant |
| One-bin tray | Tray capacity: (100 sheets), Paper size: (A4, A5, B5), Paper weight: (60-163 g/m ²) |

OTHER OPTIONS

Cabinet, High cabinet, Low cabinet, Caster table, PostScript 3, Device server unit, File format converter, OCR unit, Enhanced security HDD, Page keeper, Counter I/F unit, NFC card reader, Paperlock

CONSUMABLES

| | |
|--|---------------|
| Toner (black) | 17,500 prints |
| Toner (cyan/magenta/yellow) | 8,000 prints |
| Consumable yield based on 5% coverage/A4 | |

For availability of models, options and software, please consult your local supplier.



Ricoh Deutschland GmbH

Vahrenwalder Str. 315
30179 Hannover
Germany

+49 511 67420

www.ricoh.de