



* NOTE:All relevant materials are complied with RoHS directive.

5	UL1061 26AWG INSULATOR WIRE, LENGTH 28mm(10 pcs), LENGTH 15mm(1 pcs), DRAWING No.EH002601C-013(ID=1.0)	11	M304
	COPPER FOIL 20*60mm	1	M309
	MOLDED PE COLOR TRANSPARENT		TWN
	MOLDED PVC BLACK		M304
4	HEX-NUT UNC#4-40,4.75*8.5mm	2	M95
3	SCREW UNC #4-40, 5.0*18mm	2	M95
2	DVI(12+5) MALE, GOLD FLASH ON CONTACTS, BLACK INSULATOR	1	M83
1	HD15 FEMALE, GOLD FLASH ON CONTACTS, BLACK INSULATOR	1	M108

No.	DESCRIPTION	Q'TY	Supplier	
PART NO. 4473		Revision:		
APPROVED		Cable Length Unless Other Spec. Tolerances: 0 ~200mm ±10mm 201~1000mm ±20mm 1001 ~1500mm ±25mm 1501~2100mm ±30mm 2100mm↑ ±40mm		
CHECKED				TIAN
DRAWING				PENG
DATE	26/FEB/07	ITEM NO.	EB460	
		UNIT:mm		

CHECKED