ЛОС



# **Q27P2Q**

## 27 inch (68.6 cm) LCD MONITOR

Superior image quality and a host of features in a 27" QHD display

















3 SIDED FRAMELESS













# **Full Ergonomics**

Feel the comfort! AOC's height, tilt and swivel-adjustable stands help you find the most comfortable and healthy position.

### **Frameless**

Besides looking modern and attractive, frameless designs enable seamless multi-monitor setups. Your cursor/windows will not be lost anymore in the dark abyss of bezels, when many displays are placed side by side.



# **OHD**

With 2560 x 1440 resolution, Quad HD (QHD) offers superior picture quality and sharp imagery that reveals the finest details. The widescreen 16:9 aspect ratio provides plenty of space to spread out and work, plus allows you to enjoy games or movies in their original size.

### Wide viewing angle

Wide Viewing Angle features display color accurately at viewing angles of up to 178°. This way, it does not matter where you choose to view it from, colors will be displayed perfectly.

#### **Pivot**

Thanks to its pivot function, your monitor can be rotated by 180° from landscape into portrait mode, especially useful for desktop publishing.

#### **Three-Year Warranty**

AOC stands behind the quality of each and every monitor with a generous three-year warranty starting from the original date of purchase. Within the warranty period, any AOC displays with manufacturing defects or faulty components will be repaired or replaced at no additional charge. Read the complete AOC warranty statement for more information.

General	
Model name	Q27P2Q
EAN	4038986187961
Product Line	Pro-line
Series	P2
Channel	B2B
Classification	Superhero
Section	Business
Launch date	01/07/2020

Screen	
Resolution	2560x1440
Refresh rate	75Hz
Screen size (inch)	27 inch
Screen size (cm)	68.6 cm
Flat / Curved	Flat
Backlight	WLED
Panel Type	IPS
Aspect ratio	16:9
Display Colours	16.7 Million
Panel Colour in Bits	8
sRGB Coverage (%) (CIE 1931)	123
Adobe RGB Coverage (%) (CIE 1931)	91
NTSC coverage (%) (CIE 1931)	85 %
Active Screen Area (HxW)	596.736 (H) x335.664 (V) mm mm
Pixel Pitch	0.2331
Pixels per Inch	109
Scanning Frequency	VGA/HDMI1.4/DP1.2: 30-114 KHz (H) VGA/HDMI1.4/DP1.2 : 48-75 Hz (V)
Response time (GtG)	4 ms
Contrast (static)	1000:1
Contrast (dynamic)	50M:1
Brightness (typical)	300 cd/m <sup>2</sup>
Viewing angle (CR10)	178/178 º
Hard Glass	Antiglare + 3H
OSD languages	EN, FR , ES, PT, DE, IT, NL, SE, FI, PL ,CZ, RU, KR, CN (T), CN (S), JP

Exterior	
Monitor colour	Black
Bezel Type	Frameless
Removable Stand	*

Ergonomics	
Tilt	-5~35° °
Swivel	180 °
Pivot	1
Height Adjust Amount	150mm

Multimedia	
Audio Input	Line in
Built-in Speakers	2 W x 2
Audio output	Headphone out (3,5mm)

Connectivity and Multimedia	
Signal Input	HDMI 1.4 x 1, DisplayPort 1.2 x 1, VGA
USB input	USB 3.2 (Gen1) x 4
USB Hub	•
USB out ports	4
USB fast charge	•

What's in the Box?	
VGA cable	1,8 m
HDMI cable	1,8 m
Displayport Cable	1,8 m
Audio Cable	1,8 m
Power Cable C13	1,8 m

Power / Environmental		
Powersupply	Internal	
Powersource	100 - 240V 50/60Hz	
Power Consumption On (Energystar test method)	28 watt	
Power Consumption Standby	0.3 watt	
Power Consumption Off	0.3 watt	
EnergyClass	F	

Approbations / Regulations	
Listed on Energystar Website	¥
тсо	8
Listed on Epeat Website	1
TUV-GS	•
CE	•
FCC	×
ISO 9241-307 class l	•
Rohs compliant	1
Reach compliant	1

Warranty	
Warranty Period	3 Years

Dimensions / Weights		
Product height (mm)	544.5	
Product width (mm)	613.6	
Product depth (mm)	200.1	
Product dimensions incl base	613.6(W)x(394.5~544.5)(H)x200.1mm	
Product dimensions excl base	613.6(W)*369.5(H)*51.1(D)	
Packaging Dimensions (L x W x H)	690(W)*595(H)*160(D) mm	
Product Dimensions (incl base)	613,6*544,5*200,1 mm	
Gross Weight (including package)	8.5 Kg	
Net Weight (excluding package)	5.98 Kg	

Features	
Flicker-free	✓
Blue Light Technology	Low blue light
Kensington Lock	✓

Sustainability	
HF	•
PVC/BFR free housing	<ul> <li></li> </ul>
Mercury Free	<ul> <li></li> </ul>
Recyclable packaging material	100%
Post-consumer recycled plastic	85%